



PRODUCT-DETAILS

ACS180-04S-04A0-4

LV AC machinery drive module, IEC: Pn 1.5 kW, 4 A (ACS180-04S-04A0-4)



General Information	
Global Commercial Alias:	ACS180-04S-04A0-4
Product ID:	3AXD50000662593
ABB Type Designation:	ACS180-04S-04A0-4
Catalog Description:	LV AC machinery drive module, IEC: Pn 1.5 kW, 4 A (ACS180-04S-04A0-4)
Long Description:	The ACS180 is a compact, robust, and adaptable variable speed drive (VSD) for applications such as pumps, fans, compressors, conveyors, winders and mixers. This easy-to-use compact VSD offers excellent performance and quality at superior value with all essential machinery application features embedded. And as a member of ABB's all-compatible drives portfolio, it shares the same architecture and user interfaces for ease of use.
Display Name:	ACS180-04S-04A0-4

Ordering	
Customs Tariff Number:	85044087

HS Code:	850440 -- ELECTRICAL MACHINERY AND EQUIPMENT AND PARTS THEREOF; SOUND RECORDERS AND REPRODUCERS, TELEVISION IMAGE AND SOUND RECORDERS AND REPRODUCERS, AND PARTS AND ACCESSORIES OF SUCH ARTICLES;Electrical transformers, static converters (for example, rectifiers) and inductors;Static converters
Invoice Description:	ACS180-04S-04A0-4
Made To Order:	No
Minimum Order Quantity:	1 piece
Order Multiple:	1 piece
Quote Only:	No
Selling Unit of Measure:	piece

Dimensions

Product Net Weight:	1.24 kg
Product Net Depth / Length:	143 mm
Product Net Height:	220 mm
Product Net Width:	70 mm
Package Level 1 Depth / Length:	225 mm
Package Level 1 Height:	115 mm
Package Level 1 Width:	220 mm
Package Level 1 Units:	1 carton

Technical

Operating Point Frequency / Current	Absolute Loss	Relative Loss	Efficiency
0 / 25 %	23 W	0.8 %	86.4 %
0 / 50 %	26 W	1.0 %	91.5 %
0 / 100 %	35 W	1.3 %	93.8 %
50 / 25 %	24 W	0.9 %	92.7 %
50 / 50 %	28 W	1.0 %	95.4 %
50 / 100 %	39 W	1.4 %	96.6 %
90 / 50 %	31 W	1.1 %	97.1 %
90 / 100 %	46 W	1.6 %	97.7 %

Number of Phases:	3-phase
Degree of Protection:	IP20
Enclosure Type NEMA:	Open Type
Frequency (f):	47.5 ... 63 Hz
Frame Size:	R1
Input Voltage (U _{in}):	380 ... 480 V
Mounting Type:	Module_NO UNIT\$

Output Current, Normal Use (I_n):	4 A
Output Current, Light-Overload Use (I_{LD}):	4 A
Output Current, Heavy-Duty Use (I_{HD}):	3.3 A
Output Power, Normal Use (P_n):	1.5 kW
Output Power, Light-Overload Use (P_{LD}):	1.5 kW
Output Power, Heavy-Duty Use (P_{HD}):	1.1 kW
Apparent Power Output:	2.8 kV·A
Efficiency Level:	IE2
Standby Loss:	10 W
Temperature Rating:	Maximum 40 °C

Environmental

SCIP:	5d07f008-496e-4abd-8f50-616cb485c791 Finland
WEEE Category:	5. Small Equipment (No External Dimension More Than 50 cm)

External Classifications and Standards

UNSPSC:	39122001
---------	----------

Categories

Products > Drives > Low Voltage AC Drives > Machinery Drives > ACS180 - Machinery Drive

